**Amendments to the Claims:**

Please amend claims 1, 4, 5, and 7-11, and please add claim 12 as follows.

This listing of claims replaces all prior versions, and listings, of claims in the application.

**Listing of Claims:**

A²

1.      (currently amended)  A branch predictor for a multi-processing computer able to execute multiple processes, each process having a designated process reference, comprising:

a history register for storing a branch history of previous sequential branch instructions;

a hash logic for creating an index from a combination of a process ~~references~~ reference of a process corresponding to a current branch instruction, an address of the current branch instruction, and the branch history;

a branch prediction table for storing branch prediction reference data, and for outputting branch prediction reference data corresponding to the index created by the hash logic;

an address selection circuit for selecting one of a target address known from the current branch instruction and a next instruction of the current branch instruction to generate a branch prediction address, in response to the branch prediction reference data output from the branch prediction table; and

a branch prediction result tester for updating the branch history stored in the history register and the branch prediction reference data stored in the branch prediction table, in response to a real branch address and the branch prediction address according to an execution result of the current branch instruction.

2.      (original) The branch predictor of claim 1, wherein the branch prediction table comprises a plurality of up/down saturating counters selected by the index created by the hash logic.

3.      (original) The branch predictor of claim 1, wherein the history register comprises a shift register.

- 3 -

A2

4.    (currently amended) The branch predictor of claim 1, wherein the <u>process reference comprises a process ID corresponding to the current branch instruction, and wherein</u> the hash logic creates the index by performing an exclusive-OR operation [[to]] <u>on</u> the process ID corresponding to the current branch instruction, the address of the current branch instruction, and the branch history.

5.    (currently amended) The branch predictor of claim 1, wherein the branch prediction result tester includes a comparator for determining whether a real branch address according to [[an]] <u>the</u> execution result of the current branch instruction matches with the branch prediction address, and ~~creating~~ <u>creates</u> a control signal corresponding to the result.

6.    (original) The branch predictor of claim 5, wherein the comparator generates a control signal of logic "1" if the real branch address matches with the branch prediction address, and generates a control signal of logic "0" if the real branch address does not match.

7.    (currently amended) The branch predictor of claim 6, wherein the address selection circuit changes and outputs the real branch address ~~to the corrected~~ <u>as the</u> branch <u>prediction</u> address when the control signal is logic "0".

8.    (currently amended) The branch predictor of claim 6, wherein the <u>branch prediction table comprises an up/down counter, and wherein the up/down</u> counter increments when the control signal is logic "1", and ~~counts~~ <u>wherein the up/down counter</u> decrements when the control signal is logic "0".

9.    (currently amended) The branch predictor of claim 6, wherein <u>the history register comprises a shift register, and wherein the</u> shift register shifts the branch prediction result in a first direction by inserting the control signal.

10.     (currently amended) A ~~prediction~~ method of <u>predicting</u> a branch address of a conditional branch instruction with reference to a branch prediction table for storing branch prediction reference data <u>in a multi-processing computer able to execute multiple processes, each having a designated process ID</u>, the method comprising the steps of:

creating an index to access the branch prediction table from a combination of a process ID <u>of a process</u> corresponding to the conditional branch instruction, an address of the conditional branch instruction, and <u>a branch history comprising</u> previous sequential branch instructions;

reading branch prediction reference data from the branch prediction table in response to the index;

selectively outputting one of a target address known from the conditional branch instruction and a next address of the conditional branch instruction in response to the branch prediction reference data; and

updating the branch history and the stored branch prediction reference data in the branch prediction table in response to a real branch address according to an execution result of the conditional branch instruction.

11.     (currently amended) The method of claim 10 further comprising the steps of:

determining whether the real branch address matches with the branch prediction address; and

changing and outputting [[the]] <u>a</u> corrected branch address [[to]] <u>as</u> the branch <u>prediction</u> address if the real branch address does not match therewith.

12.     (new) The method of claim 10, wherein creating the index comprises performing an exclusive-OR operation on the process ID of the process corresponding to the conditional branch instruction, the address of the conditional branch instruction, and the branch history comprising previous sequential branch instructions.